

UNI-SCREED

VIBRATORY SCREED



**THE BEST ONE-MAN
VIBRATORY SCREED**

TECHNICAL SPECS

Handle	28lbs (12.7kg)
Blades	
4' (1.2m)	6.4lbs (2.9kg)
6' (1.8m)	9.6lbs (4.4kg)
8' (2.4m)	12.8lbs (5.8kg)
10' (3m)	16lbs (7.3kg)
12' (3.7m)	19.2lbs (8.7kg)
14' (4.5m)	22.4lbs (10.2kg)
16' (4.9m)	25.6lbs (11.6kg)
Engine	GX35
Fuel Capacity	0.17 Gal (0.65L)
Estimated Running Time	1.1hrs @ 7000rpm
Weight (dry)	27.9lbs + blade (12.7kg + blade)
Weight (operating)	29.6lbs + blade (13.5kg + blade)
Sound Power	50 Dba
Vibration	<9 m/s ²

FEATURES

- Specially designed to permit a single operator to quickly and easily level an entire area.
- Adjustable handle to meet operator needs and more efficient handling.
- Handle vibration is minimized with our impact absorbing mounting system to optimize control and operator comfort.
- Superior control is achieved with our responsive handle mounted throttle and on/off switch.
- High frequency vibration disperses and levels concrete without build-up.
- Lightweight, easy to transport to and around job sites.
- Blade design permits cutting and smoothing in a single operation.
- Interchangeable blades with other leading wet screed units.



UNI-SCREED



STANDARD SCREED



SUPER SCREED